



Customer:  
Order Date:  
Order Number:

Series Description: UNDERFLOOR  
Model Description: KNOSSOS 50  
Model Version: SF 230  
Drawing Code: 004.55.00003  
Drawing Date: 02/02/2016

MACHINE PROPERTIES						
Capacity (LT)		Weight (KG)		Voltage (V)	Max. Amp./Phase	Max. Loading (KW)
Boiler	Tub	Net	Gross			
6	35	63	66	230V-1N-50/60 Hz	15.6	3.6

A/A	DESCRIPTION	BUBBLE INFORMATION	NOTE
1.	Electrical Supply Connection cable Pos.		PVC Coated H05 VVF 3 X 2,5mm, Cable Length = 2m (witout connector)
2.	Draining Pipe (1,6m) Ø28 Outer Ø24 Inner Pos.		Used Only for Free Flow , Drainage Without Pump
2.1	Draining Pipe (1 m) Ø25 Outer Ø20 Inner Pos.		Only With Draining Pump Included (Hman = 0,7m MAX)
3.	Inlet Male Nozzle Threaded end G3/4" for Water Supply		To Flexible Pipe Water Inlet Threaded Female Ends G 3/4" (Flexible Pipe Length = 1,5m)
4.	Rinse Aid Flexible Pipe Pos. (Blue Color)		Outer Diameter Ø6 x 1400mm Length
5.	Detergent Flexible Pipe Pos. (Crystal Color)		Outer Diameter Ø6 x 1400mm Length
6.	Control Panel		

Various Information: