



MACHINE PROPERTIES					BALLOON INFORMATION		<b>ELVIOMEX</b>  INSTALLATION DRAWING MODEL 600
<b>CAPACITY (Lt)</b>		<b>WEIGHT (Kg)</b>		<b>VOLTAGE (V)</b>	1.	Electrical Supply 1.75 m Connection 1N : H05 VV-F 3x2.5mm, Cable length without plug : 1.3m 3N : H05 VV-F 5x2.5mm, Cable length without plug : 1.3m	
<b>Boiler</b>	<b>Tank</b>	<b>Net</b>	<b>Gross</b>	220-240 V - 1N-50/60Hz	2.	Draining pipe (1.0m) OD25-ID20 (with draining pump)	
6	9	70	75	380-415 V - 3N-50/60Hz	3.	Inlet Male Nozzle Threaded End G3/4" for Water Supply(Pipe length : 1.5m)	
<b>Max.Amp./Phase(A)</b> : 1N- 15.4 3N- 12.2		<b>Max.Loading (KW)</b> : 1N- 3.6 3N- 6.6			4.	Rinse Aid Flexible Pipe Pos.(Blue) (Outer Diameter 6mm - L:1.5m)	
					5.	Detergent Flexible Pipe Pos. (Clear) (Outer Diameter 6mm - L:1.5m)	